

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.


As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G02B 5/30, B42D 15/10, G02F 1/1337, 1/1333		A1	(11) International Publication Number: WO 99/53349
			(43) International Publication Date: 21 October 1999 (21.10.99)
(21) International Application Number: PCT/IB99/00590 (22) International Filing Date: 6 April 1999 (06.04.99) (30) Priority Data: 841/98 9 April 1998 (09.04.98) CH (71) Applicant (for all designated States except US): ROLIC AG [CH/CH]; Innere Güterstrasse, CH-6301 Zug (CH). (71)(72) Applicant and Inventor: SCHADT, Martin [CH/CH]; Liestalerstrasse 77, CH-4411 Seltisberg (CH). (72) Inventors; and (75) Inventors/Applicants (for US only): SEIBERLE, Hubert [DE/DE]; Bodenseestrasse 1, D-79576 Weil am Rhein (DE). MOIA, Franco [IT/CH]; Eggstrasse 24A, CH-4402 Frenkendorf (CH). (74) Agent: NEVILLE, Peter, Warwick; BTG International Ltd., 10 Fleet Place, Limeburner Lane, London EC4M 7SB (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: OPTICAL IDENTIFICATION ELEMENT



(57) Abstract

An optical component in the form of an identification element, especially for counterfeit protection and copy protection, has an optically anisotropic layer (4) having regions of different optical axes that is arranged over a reflector (2). The anisotropic layer (4) consists preferably of a liquid crystal polymer in which the orientation of the liquid crystals is different in different areas. This orientation pattern is initially hidden from a viewer, but becomes visible by means of an additional polariser. To improve the visual appearance of the identification element, a white light hologram is used as reflector (2).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

Optical identification element

The invention relates to an optical identification element, especially for counterfeit protection and copy protection, comprising at least one optically
5 anisotropic layer, which has at least two regions having different preferred directions, and a layer that is at least partially reflective.

The demands made of the protection of items such as banknotes, credit cards, securities, identity cards and the like against counterfeiting are constantly increasing
10 as a result of the availability of high quality copying techniques. In addition, pirated copies of branded products, such as compact discs, computer software, electronic chips and so on, are increasingly being produced and distributed worldwide. On account of the growing number of instances of counterfeiting there is accordingly a great need for new, counterfeit-protected elements that can be identified both visually
15 and by machine.

In recent years, new types of counterfeit-protected identification elements that utilise liquid crystals and associated optical effects have become known. Examples thereof are described in EP-A-0 689 065 and WO-A-98/52077, the disclosures of
20 which are hereby incorporated by reference.

Such identification elements are based on a hybrid layer structure which comprises a layer having molecules that are fixed (crosslinked) in the liquid-crystalline state, which layer is optically anisotropic and usually acts as an optical
25 retarder. In the production of that layer the orientation of the liquid crystal molecules can be preset to be different in different areas, preferably by means of a correspondingly structured orientation layer, such as can be produced, for example, from a linearly photopolymerised polymer network. The result is an optically structured, fixed liquid crystal layer having an orientation pattern that has been determined in

advance. When viewed without an additional aid, the orientation pattern, i.e. the information thus recorded in the liquid crystal layer, is initially invisible. The layers appear in this case to be transparent. The orientation pattern becomes visible only when the identification element is placed between two polarisers.

5

In especially suitable arrangements of such counterfeit-protected identification elements, the optically structured liquid crystal layer is located over a reflective background. This makes it possible for the orientation pattern, i.e. the corresponding information, to be rendered visible using only one polariser which is held above the element.

10

As the reflective background (referred to hereinafter as the reflector) there have been used hitherto materials such as diffuse or mirroring metal surfaces, reflective lacquers, reflective paper or the like. In that case the mode of operation of the identification elements usually requires the incident light to retain its polarisation state, at least to a certain extent, on reflection at the reflector.

15

A disadvantage of the reflectors known hitherto for the said identification elements is that brightness and contrast are lost to a comparatively great extent on reflection.

20

According to the invention it is therefore proposed to use a holographic reflector. This type of reflector, known *per se*, reflects (and focuses) the ambient light into a predetermined cone of diffuse light and thus produces a substantial increase in brightness in the region of the cone. At the same time, dazzling reflections (glare) are largely avoided and an excellent brightness distribution is obtained. In addition, the polarisation is almost completely retained. These properties bring about a crucial improvement in the visual appearance of the identification elements, which is important both for the actual identification and its ability to be discerned and for

25

market acceptance. Thus, according to the invention, there is provided optical identification element, especially for counterfeit protection and copy protection, comprising at least one optically anisotropic layer, which has at least two regions having different preferred directions, and a layer that is at least partially reflective, characterised in that the at least partially reflective layer is a holographic reflector

Surprisingly, tests have shown that holographic reflectors, despite their complex structure, do not have an adverse effect on the mode of action of the identification element, which will usually likewise be of comparatively complex structure.

The reflector is preferably based on an achromatic, or white light, hologram, that is to say the predetermined cone of diffuse light produced by the holographic reflector is substantially white.

For the sake of simplicity the opening explanation, of the structure and principle of operation of counterfeit-protected identification elements having an optically structured, fixed liquid crystal layer was limited to basic principles. However, a large number of arrangements that are more complex in terms of structure and optical mode of action exist, some of which are described in the publications mentioned above, and it is possible to imagine other arrangements operating in accordance with the same basic principles. For example, it is possible additionally to integrate one or more polariser layers, for example in the form of a liquid crystal layer containing dichroitic dyes or in the form of a conventional polarisation film, it also being possible for a polariser to contribute to the information recorded in the element when the polarisation properties are different in different areas. Also possible are combinations of two or more information-carrying liquid crystal layers and optionally associated polariser layers, or alternatively configurations having cholesteric filters, especially for producing different colours. It will be clear to the person skilled in the

art that all those arrangements and similar arrangements of counterfeit-protected identification elements, where they are used in reflection, will benefit from the above-mentioned advantages and are covered by the present invention.

5 According to a special embodiment of the invention, the holographic reflector is transfective or partially transparent. This enables, for example, an identification element according to the invention to be mounted over a visible feature, which nevertheless remains visible as a result of the partial transparency of the reflector.

10 Preferably, the optically anisotropic layer is formed with liquid crystal molecules that are substantially fixed in their orientation. The layer may be formed with a layer of crosslinked liquid-crystalline monomers, oligomers or polymers. An orientation layer may be provided for this liquid crystal molecules, preferably formed from a linearly photopolymerised polymer network.

15 The invention extends to an item such as a banknote or identity card with protection against forgery and/or copying, characterised by an optical identification element as set forth above.

20 A method of checking such an element for authenticity may comprise passing light through a polariser onto the optical component and viewing the reflected light from this layer through the polariser.

25 The invention will now be described by way of example, by the following embodiments. The accompanying drawings show, in simplified form,

Fig. 1 an identification element according to the invention;

Fig. 2 a further variant of a layer structure for an identification element according to the invention, and

Fig. 3 a diagram showing various possible combinations of the orientation of the optical axes in the retarder layers of Figure 2.

Figure 1 shows diagrammatically a cut-away view of a layer structure (2, 3, 4) of an identification element according to the invention which is arranged on an article to be protected against counterfeiting or illegal copying, for example on a banknote. The height of the element is shown exaggerated; it is usually only a few tens of micrometres. The base or substrate of the layer structure is a paper layer 1 which, in the case of a banknote, will be identical with the banknote paper. In a certain region of the paper there is a reflector 2. Mounted on the reflector is an orientation layer 3 on which in turn a retarder layer 4 is mounted. The retarder layer 4 has regions having different optical axes (indicated by rectangular divisions in the Figure) which form an orientation pattern. When the configuration is viewed through a (separate) polarisation filter 5, the pattern becomes visible.

The reflector 2 is important for the optical action of the identification element when viewed through the polarisation filter, the reflector here being a holographic reflector, more specifically a film carrying a white light hologram, as available in various variants, for example, from the Polaroid company under the name LIFT.

Further details of the embodiment shown in Figure 1 will be found below.

25


The orientation layer 3 is a so-called "linearly photopolymerised" (LPP) orientation layer, sometimes also referred to as "photooriented polymer networks" (PPN), which is differently oriented in different areas. Suitable materials for this purpose are *inter alia* cinnamic acid derivatives, as described, for example, in the

published specifications EP-A-525 478 and US-5 389 698. The orienting and simultaneous crosslinking thereof is effected in known manner by selective irradiation with linearly polarised UV light.

5

The preparation can be carried out, for example, as follows: the LPP material used is

Poly [1-methyl-1-(2-oxo-2H-1-benzopyran-7-yloxy-carbonyl)-ethylene]



10


A synthesis procedure is described under Example 1 of International Patent Application WO-96/10049. The reflector 2 is coated by spin-coating with a 3 % solution of the LPP material in a solvent, for example N-methylpyrrolidone (NMP), for one minute at 2000 rev/min. The layer is then dried for 30 minutes on a hotplate at 130°C. The orienting and crosslinking can then be produced by irradiation with the linearly polarised light of a 200W extra high pressure mercury vapour lamp for approximately 5 minutes at room temperature. If, during that procedure, some regions are irradiated with a certain polarisation direction and other regions with a polarisation direction rotated relative thereto, the pattern obtained will have regions of different orientation.

20

An optically anisotropic layer with preferred directions, in the form of an anisotropic layer of crosslinked liquid crystal monomers, forms the retarder layer 4. This LCP layer (LCP = Liquid Crystal Polymer) has a molecular arrangement the orientation of which has been preset by the orientation of the underlying orientation

5 layer 3.

The following diacryl components, for example, may be used as crosslinkable liquid crystal monomers for the LCP layer:



When composed of 80% Mon1, 15% Mon2 and 5% Mon3, these diacrylate monomers yield a supercoolable, nematic mixture having a low melting point ($T_m \sim 35^\circ\text{C}$) that allows the preparation of the LCP layer to be carried out at room temperature. By adding 2% of the photoinitiator Irgacure 369 from Ciba-Geigy ("Irgacure" is a Trade Mark) it is possible to accelerate the subsequent crosslinking process. If this mixture is dissolved in anisole it can be applied to the orientation layer by spin-coating, the LCP layer thickness being adjustable within a wide range

especially by way of the concentration of the solution. For the crosslinking of the liquid crystal monomers, it is then possible to carry out irradiation with isotropic light from a 200W extra high pressure mercury vapour lamp for about 1 minute in an inert atmosphere.

5

Figure 2 shows a further possible layer structure for an identification element according to the invention. The reference numeral 10 indicates a reflector which can be of the same construction as in Figure 1. In contrast to Figure 1, in this variant two orientation/retarder layer pairs are arranged one above the other, namely a
10 first orientation layer 11, a first retarder layer 12, a second orientation layer 13 and a second retarder layer 14. With this configuration it is possible to produce a multi-coloured pattern when, in addition to different optical axes in different regions of the same retarder layer, also the orientations of the optical axes of regions lying above one another in the retarder layers 12 and 14 are differently combined. For this
15 purpose the two retarder layers advantageously have non-identical optical retardation.

An example of different combinations of the relative orientation of the optical axes of regions lying above one another in the retarder layers 12 and 14, with which a different colour can be obtained for each combination, is shown in the
20 diagram of Figure 3.

Claims

1. Optical identification element, comprising at least one optically anisotropic layer (4, 12, 14), which has at least two regions having different preferred directions, and a layer (2, 10) that is at least partially reflective, characterised in that the at least partially reflective layer (2, 10) is a holographic reflector.
2. Optical identification element according to claim 1, characterised in that the reflector (2, 10) is substantially achromatic.
3. Optical identification element according to claims 1 or 2, characterised in that the reflector (2, 10) is transfective or partially transparent.
4. Optical identification element according to any preceding claims, characterised in that the optically anisotropic layer (4, 12, 14) is formed with liquid crystal molecules of substantially fixed orientation.
5. Optical identification element according to claim 4, characterised in that the optically anisotropic layer (4, 12, 14) is formed with a layer of crosslinked liquid-crystalline monomers, oligomers or polymers.
6. Optical identification element according to claims 4 or 5, characterised by an orientation layer (3, 11, 13) for liquid crystal molecules.
7. Optical identification element according to claim 6, characterised in that the orientation layer (3, 11, 13) is formed from a linearly photopolymerised polymer network.

Fig. 1




Fig. 2





Fig. 3



INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 99/00590

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G02B5/30 B42D15/10 G02F1/1337 G02F1/1333

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G02B B42D G02F G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 694 229 A (DRINKWATER KENNETH JOHN ET AL) 2 December 1997 see column 3, line 44 - column 4, line 44 see column 11, line 16 - line 52	1-3, 8, 9
A	EP 0 689 065 A (HOFFMANN LA ROCHE) 27 December 1995 cited in the application see page 2, line 29 - page 3, line 28; claims 1-4, 10, 12-15; figure 1; example 3	1-9
A	EP 0 772 069 A (ROLIC AG) 7 May 1997 see page 3, line 3 - page 4, line 5; figures 1-5	1, 4-9
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 June 1999

Date of mailing of the international search report

21/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

THEOPISTOU, P

INTERNATIONAL SEARCH REPORT

Int. l. Application No.

PCT/IB 99/00590

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 721 630 A (HORNER M GLENN ET AL) 24 February 1998 see column 4, line 62 - column 5, line 39 see column 6, line 13 - line 47 see column 9, line 1 - column 10, line 19; figures 1,2,19; example 5	1-3
A	EP 0 689 084 A (HOFFMANN LA ROCHE) 27 December 1995 see page 4, line 12 - page 5, line 9; figures 1-5	1,4-9
A	WO 95 12826 A (MOTOROLA INC) 11 May 1995 see page 13, line 12 - page 14, line 15; figure 9	2,3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 99/00590

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5694229 A	02-12-1997	AT 170135 T DE 69320624 D DE 69320624 T EP 0632767 A ES 2122007 T WO 9324333 A JP 7507245 T	15-09-1998 01-10-1998 14-01-1999 11-01-1995 16-12-1998 09-12-1993 10-08-1995
EP 0689065 A	27-12-1995	CN 1116754 A JP 8043804 A	14-02-1996 16-02-1996
EP 0772069 A	07-05-1997	CN 1152134 A JP 9179126 A	18-06-1997 11-07-1997
US 5721630 A	24-02-1998	CA 2213319 A EP 0826160 A WO 9734174 A	18-09-1997 04-03-1998 18-09-1997
EP 0689084 A	27-12-1995	CN 1130259 A JP 8015681 A SG 34990 A	04-09-1996 19-01-1996 01-02-1997
WO 9512826 A	11-05-1995	AU 686279 B AU 1082995 A CA 2151056 A CN 1116003 A EP 0677173 A JP 8505716 T US 5663816 A	05-02-1998 23-05-1995 11-05-1995 31-01-1996 18-10-1995 18-06-1996 02-09-1997